

Photo Papers

|               |
|---------------|
| Toner         |
| <b>Water</b>  |
| (eco) Solvent |
| UV Curable    |
| Latex         |

# IJM262(C) Instant Dry Photo Paper, Satin 190 g/m<sup>2</sup>

**Product Description**

Instant-dry, satin, bright white photo paper with a microporous coating, on a high-opacity PE-coated base.

**Physical Properties**

|                            |     |         |            |                 |          |
|----------------------------|-----|---------|------------|-----------------|----------|
| Thickness (µm)             | 185 | ISO 534 | L*; a*; b* | 96.0; 1.8; -6.0 | DIN 6174 |
| Weight (g/m <sup>2</sup> ) | 190 | ISO 536 |            |                 |          |

**Applications/features**

- High-quality photos
- Indoor signage (posters, point of purchase)
- Exhibition graphics
- Short-term outdoor signage (when laminated)
- Instant dry
- Excellent colour reproduction
- Bright white appearance
- High colour density and image sharpness
- Good lamination properties

**Available Widths (mm)**

|                    |     |     |      |      |      |  |  |  |  |  |  |
|--------------------|-----|-----|------|------|------|--|--|--|--|--|--|
| 3"core + 2"adapter | 610 | 914 | 1067 | 1270 | 1524 |  |  |  |  |  |  |
|--------------------|-----|-----|------|------|------|--|--|--|--|--|--|

Refer for our current offering to [mediaguide.oca.com](http://mediaguide.oca.com)

**Storage Conditions**

Shelf life: 2 years, Temperature 15-25°C, Relative Humidity 30-70%  
 Repack opened rolls when not in use.

**Print Conditions**

Best results are obtained at 23°C and 50% RH.  
 Higher humidity will increase drying time, low humidity may cause curling.

**Environment, Health & Safety**

No Material Safety Data Sheet required. Paper waste is not suitable for recycling.

**Lamination Compatibility**

|      |      |     |  |
|------|------|-----|--|
| Cold | Warm | Hot | Cold: pressure sensitive<br>Warm: heat activated: 85°C - 95°C<br>Hot: heat activated: 105°C -130°C |
| yes  | yes  | no  |  |

**Outdoor Use**

This photo paper is not suitable for outdoor use. Short time outdoor use possible only when laminated.

**Colour Profiles**

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.  
 Check availability of profiles for your printer on [mediaguide.oca.com](http://mediaguide.oca.com)



---

**Processing  
Guidelines**

**Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing.  
Keep out of direct sunlight.  
Side to be printed is the outer side of the roll.  
Use of gloves is recommended.  
Dye inks on microporous coated products can exhibit some fading (apart from UV) due to its open structure. Gasses like Ozone cause this phenomenon. Lamination will solve this issue.

**Lamination guidelines**

Immediate lamination possible.  
One-sided lamination may cause curling.

---

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.