SAT912 Top Colour Digital - FSC® 90 g/m^2

Product Description

Top Colour Digital is a high quality woodfree uncoated satinated paper providing excellent print results. The high whiteness and smooth surface enables vibrant quality and impressive text and image details. Designed for all your full colour applications.

Physical Properties

Weight (g/m^2)	90	ISO 536	Opacity (%)	93.5	Elrepho
Thickness (μm)	94.5	ISO 534	Brightness (%)	114	ISO 24702
Whiteness	170	CIE	Roughness**	50 ml/min	Bendtsen ISO 8791

*MD/CD **WS/TS

Features

Top Colour Digital is the ideal product for a full range of colour applications such as letters, direct mail, reports, presentations as well as coupons, manuals, books, and brochures.

Available Sizes

	A4	A3	SRA3
Grain direction	LG	SG	SG

LG = Long grain, SG = Short grain

Storage Conditions

Temperature 10 - 30 °C, Relative Humidity 20 - 70%
Repack opened reams or boxes when not in use.

Print Conditions

Acclimatize paper 24 hours before printing in print room conditions (preferably next to printer)
Best results are obtained between 15-25 °C and 30-65% RH (relative humidity)

Environment, Health & Safety

No Material Safety Data Sheet required.
ISO 9001 and 14001 certified production site.
ISO9706 Permanent Paper certified.
Paper waste is suitable for recycling in most countries. Please refer to local paper recycle station.

Processing Guidelines, Tips & Tricks

No special runnability advice.

Environmental Certification

FSC
www.fsc.org
MIX
Paper from responsible sources
FSC® C008945

EU Ecolabel
www.ecolabel.eu

ISO 9706

Canon

Canon

Canon